



Video Splitter

4-port

Model
177214

Direct a single video signal to multiple monitors.

From a single source, distribute your signal to multiple VGA displays synchronously to ensure that the different displays show the same image. High bandwidth, resolution and, of course, MANHATTAN reliability make this the perfect solution for securities business, exhibition halls, public broadcasting, education and training centers.

Flexible solution for many applications

Ideal for trade shows, classrooms, video conferencing and presentations, the MANHATTAN Video Splitter features two ports with a built-in booster for added signal strength. MANHATTAN high-quality features include gold-plated contacts, a fully shielded metal case and anti-skid feet.

Easy to install

Simply connect cables to display a signal on multiple monitors. No software or hardware configuration required.

Quality construction

Durable metal housing keeps the unit safe from impact and other environmental damage. High-quality connections provide you with clean signal output.

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all MANHATTAN products. All items carry a full Lifetime Warranty — the strongest quality commitment anyone can make.





Model
177214

Features

- Directly insert SATA
- Duplicates a high-definition digital audio/video signal for up to eight HDMI outputs
- Delivers a sharp, clear signal from DVD and Blu-ray players, set-top box, satellite receiver and other sources
- Fully HDCP compliant to protect high-definition content transmission and ensure quality reception
- Cascade up to three levels to expand signal distribution to more displays
- Durable, compact metal housing ideal for crowded equipment rooms and cabinets
- Easy to install — requires no configuration
- Lifetime Warranty/ L-type drives into a desktop PC bay — no internal tray required
- Space-saving design fits three • Duplicates a high-definition digital audio/video signal for up to four HDMI outputs
- Delivers a sharp, clear signal from DVD and Blu-ray players, set-top box, satellite receiver and other sources
- Fully HDCP compliant to protect high-definition content transmission and ensure quality reception
- Cascade up to three levels to expand signal distribution to more displays
- Durable, compact metal housing ideal for crowded equipment rooms and cabinets
- Easy to install — requires no configuration
- Lifetime Warranty4." drives in two 00.25" bays
- Patented connector reduces damage to drive pins for many reliable connections
- Hot-swappable — ideal for transporting data between multiple locations and PCs
- Unique case and built-in fans maximize airflow and cooling efficiency
- Anti-vibration construction protects drives from shock
- Lifetime Warranty

Specifications

Standards and Certifications

- CE
- FCC
- ISO 9002

General

- Power LED
- Computer-to-video splitter range: 7.5 m (25 ft.)
- Video splitter-to-monitor range: 50 m (165 ft.)
- Power: 9 V DC / 300 mA; cable, 1.6 m (5.5 ft.)

Connections

- 1 HD15 male (input)
- 4 HD15 female (output)

Signal

- Signal support: VGA, SVGA, Multisync
- VGA bandwidth: 150 MHz
- VGA resolution: 1600 x 1280
- Min./max. input voltage: 0.5 V p-p / 1.0 V p-p
- I/O impedance: 75 Ohms
- Horizontal frequency: 30-120 kHz
- Vertical frequency: 40-120 kHz

Physical:

- Dimensions: 54 x 208 x 104 mm (2.1 x 8.2 x 4 in.)
- Weight: 700 g (24.7 oz.)
- Housing: Metal

Package Contents

- Video Splitter
- Power adapter and user manual

For more information on MANHATTAN products, consult your local dealer or visit www.manhattan-products.com.


MANHATTAN
BRINGING COMPUTERS TO LIFE

Copyright © MANHATTAN

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

MH-177214-DS-0821-01