

Xonar DGX

- **Audio Interface**

PCI Express

- **Audio Performance**

Output Signal-to-Noise Ratio (A-Weighted) (Front-out) :

105 dB

Input Signal-to-Noise Ratio (A-Weighted) :

103 dB

Output THD+N at 1kHz (Front-out) :

<0.0025 %(-92 dB)

Input THD+N at 1kHz :

<0.0022 %(-93 dB)

Frequency Response (-3dB, 24bit/96KHz input) :

10 Hz to 48 KHz

Output/Input Full-Scale Voltage :

- **Chipset**

Audio Processor : C-Media CMI8786 High-Definition Sound Processor (Max. 96KHz/24bit)

- **Sample Rate and Resolution**

Analog Playback Sample Rate and Resolution :

44.1K/48K/96KHz @ 16bit/24bit

Analog Recording Sample Rate and Resolution :

44.1K/48K/96KHz @ 16bit/24bit

S/PDIF Digital Output :

44.1K/48K/96KHz @ 16bit/24bit

- **Capacidades Especiales**

Smart Volume Normalizer™

Xear 3D™ Virtual Speaker Shifter

Magic Voice™

Karaoke Functions

FlexBass™

10 -band Equalizer

27 Environment Effects

GX 2.5 Game Audio Engine

VocalFX™

- **Accesorios**

Low -profile Bracket x 1

Driver CD x 1

Quick Start Guide x 1

- **Dimensiones**

170.44 x 64.39 mm (L x W)