

## SkyIPCam500W Wireless Night Vision Network Camera



- High-quality Day & Night Vision with Infrared LED and auto light sensor control
- Remote access from Web browser over Internet for live video/audio surveillance
- Embedded Web UI configuration with ID/Password protection
- Supports digital Zoom, time stamp overlay, and mirror functions
- Motion Detection with 2 Adjustable Windows
- Supports IEEE802.11b/g wireless connectivity with WEP(64/128 bit), WPA-PSK, and WPA2-PSK security settings



[Enlarge Image](#)

The SkyIPCam500W supports real-time high quality video and audio over the Internet with built-in omni-directional microphone. The high-quality Infrared lens provides night monitoring for low light environment. Powerful application software "Airlink101 SkyIPCam View" supports simultaneous live view, snapshot, and video recording up to 16 Cameras. The SkyIPCam500 Supports FTP uploading and email notification with images triggered by motion detection or by Schedule.

### Specifications

Image Sensor	Sensor Type : 1/4" Color CMOS Sensor Sensor Resolution : 640 x 480 pixel Minimum Illumination : 0.5 Lux
Infrared LEDs	Triggered by Auto Light Sensor
Lens	Lens Type : Board Lens View Angle (Diagonal) : 60 degree
Video	Image Compression : MJPEG Auto Exposure Control : Yes Auto White Balance : Yes Auto Gain Control : Yes Image Resolution and Frame Rate: - VGA (640 x 480): 30fps - QVGA (320 x 240): 30fps - QQVGA (160 x 120): 30fps
Audio	Input : Internal Omni-directional Microphone
Communication	Ethernet : one 10/100Mbps RJ-45 Wireless : IEEE802.11b/g Supported Protocols : TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, PPPoE, UPnP
Interface & Buttons	DC Power Connector Ethernet Cable Connector Reset Button



### System Requirements

- OS Supported : Windows 2000/XP/Vista
- Browser : Internet Explorer 6.0 or above  
Apple Safari 2 or above  
Mozilla Firefox 2.00 or above

### Package Contents

- SkyIPCam500W Wireless Night Vision Network Camera
- Power adapter
- Ethernet cable (RJ-45)
- Camera stand
- Utility CD
- Quick installation guide



LED	Power LED : Orange Color Link/Act. LED : Green Color
Power	Output : DC 5V / 2.5A Power Consumption : 6 watts Max.
Environment	Operating Temperature : 0°C ~ 45°C Operating Humidity : 20% ~ 85% non-condensing Storage Temperature : -15°C ~ 60°C Storage Humidity : 0% ~ 90% non- condensing
Certification	FCC, CE
Warranty	Limited 1-year warranty

[How It Works / Comment ça marche](#)



\* Theoretical maximum wireless signal rate based on IEEE standard 802.11g specifications.

\* Actual throughput will vary. Specifications are subject to change without notice. All products and trademarks are the property of their respective owners. Photos of product may not reflect actual content. Copyright ©2010 Airlink101®