

MEJOR VENDIDO



## PUC6004BU-FE

### Cable de cobre

Los cables de cobre, de categoría 6 mejorada UTP, CM, 4 pares, tienen una construcción de 23 AWG con aislamiento de HDPE, trenzados por pares, separados por un divisor de pares integrado y protegidos por una chaqueta de PVC ignífuga, azul.



## Presupuesto

Longitud total (pies)	1000
Largo total (m)	305
Material de la chaqueta	Cloruro de polivinilo
Calibre del conductor (AWG)	23
Diámetro nominal (pulg.)	0.225
Diámetro nominal (mm)	5.7
Diámetro de aislamiento (pulg.)	0.04
Cantidad de pares	4
Sub marca	PanNet
Temperatura de funcionamiento máxima (° C)	60
Temperatura de funcionamiento máxima (° F)	140

Temperatura de funcionamiento mínima (° C)	-20
Temperatura de funcionamiento mínima (° F)	-4
Temperatura de instalación máxima (° F)	122

Tipo de paquete	Cartón de fácil pago
Color	Azul
Grado de inflamabilidad	CM
Longitud (pies)	1000
Solicitud	Interior
Tipo de cable	U / UTP
Diámetro máximo del aislamiento del alambre (mm)	1.2
Nota	Disponible en Asia Pacífico y Sudamérica
Características de la parte	Terceros probados, rendimiento de canal garantizado por encima de los estándares, divisor cruzado, probado más allá de los estándares y marcas de cable de longitud descendente





Nivel de desempeño	Categoría 6
Estado de conformidad RoHS	Obediente
Min. Cantidad.	24

## detalles del empaque

UPC	07498387841
Std. Pkg. Qty.	1
Std. Pkg. Volumen (cf)	1.9367
Std. Ctn. Qty.	24
Std. Ctn. Volumen (cf)	46.4813

## Recursos

<p>Informes de tecnología</p>	<p>Alimentación por Ethernet con cableado de cobre Panduit</p>	<p>Inglés americano</p>	<p>PDF 562.98KB (/content/dam/panduit/en/products/assets/p/pu/puc/puc6/puc6004bufe/media/D-COTB05--WW-ENG-POEwithPCC.pdf)</p> <p> (/content/dam/panduit/en/products/assets/p/pu/puc/puc6/puc6004bufe/media/D-COTB05--WW-ENG-POEwithPCC.pdf)</p> <p></p>
<p>Hojas de especificaciones</p>	<p>Cable de cobre U / UTP Categoría 6 mejorada TX6000™ COSP378 - WW-ENG</p>	<p>Inglés americano</p>	<p>PDF 96.29KB (/content/dam/panduit/en/products/assets/p/pu/puc/puc6/puc6004bufe/media/D-COSP378--WW-ENG-TX6000Cat6UUTPCperCbl-W.pdf)</p> <p> (/content/dam/panduit/en/products/assets/p/pu/puc/puc6/puc6004bufe/media/D-COSP378--WW-ENG-TX6000Cat6UUTPCperCbl-W.pdf)</p> <p></p>
<p>Guías de selección</p>	<p>Category 6 UTP Copper Cabling System Selection Guide</p>	<p>US English</p>	<p>PDF 1.07MB (/content/dam/panduit/en/products/assets/p/pu/puc/puc6/puc6004bufe/media/D-COSG13--WW-ENG-Cat6UTPCopperSelectGde-W.pdf)</p> <p> (/content/dam/panduit/en/products/assets/p/pu/puc/puc6/puc6004bufe/media/D-COSG13--WW-ENG-Cat6UTPCopperSelectGde-W.pdf)</p> <p></p>

Certifications	ETL PUC6004 Channel Report of Test Certificate 6 Conn.	US English	<p>PDF 89.47KB (/content/dam/panduit/en/products/assets/p/pu/puc/puc6/puc6004bufe/media/D-CORP1--WW-ENG-ETL-PUC6004BU-FEChannel.pdf)</p> <p> (/content/dam/panduit/en/products/assets/p/pu/puc/puc6/puc6004bufe/media/D-CORP1--WW-ENG-ETL-PUC6004BU-FEChannel.pdf)</p> <p></p>
System Warranty	Guaranteed Performance Beyond the Standards TX6000™ UTP Copper Cabling Systems : COFL13	US English	<p>PDF 921.85KB (/content/dam/panduit/en/products/assets/p/pu/puc/puc6/puc6004bufe/media/D-COFL13--WW-ENG-CAT6UTP-HeadrmWarnty-W.pdf)</p> <p> (/content/dam/panduit/en/products/assets/p/pu/puc/puc6/puc6004bufe/media/D-COFL13--WW-ENG-CAT6UTP-HeadrmWarnty-W.pdf)</p> <p></p>

## Related Products



## PUP6C04WH-U

Category 6 copper cable, plenum (CMP), 4-pair, U/UTP, conductors are 23 AWG construction with FEP/polyolefin insulation, twisted in pairs, separated by a tape, and protected by a low smoke, flame-retardant PVC jacket, white.

(</en/products/copper-systems/cable/cable/pup6c04whu.html>)



## PUP5C04WH-U

Copper cable, category 5e U/UTP, plenum (CMP), 4-pair, conductors are 24 AWG construction with FEP/polyolefin insulation, twisted in pairs and protected by a low smoke, flame-retardant PVC jacket, white.



(/en/products/copper-systems/cable/cable/pup5c04whu.html)



**PUP6504BU-UY**

Copper cable, premium category 6 UTP, plenum (CMP), 4-pair, conductors are 23 AWG construction with FEP insulation, twisted in pairs, separated by an integrated pair divider and protected by a low smoke, flame-retardant PVC jacket, blue.

(/en/products/copper-systems/cable/cable/pup6504buuy.html)



### Email Support

Email support available 24/7

(/en/support/contact-us.html)



### 01 800 460 86 00

Monday through Friday 8am-6pm


(tel:800-777-3300)



### Where to Buy

Find a Panduit Distributor or Partner

(/en/support/where-to-buy/find-a-distributor.html)



### GET OUR CATALOG

Download the PDF or request a copy be mailed to you.

Which catalog would you like? ▼

▶ DOWNLOAD ▶ REQUEST COPY



(<https://www.facebook.com/Panduit>)



(<https://plus.google.com/+panduit>)



(<https://twitter.com/Panduit>)



(<https://www.youtube.com/user/PanduitVideos>)



(<http://us.linkedin.com/company/panduit>)

Copyright 2018 Panduit