


ThinkCentre M93p Mini Tower (10A6) - GMP

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ⁸	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Additional Front USB 2.0	2nd serial port	Chassis intrusion switch	Intel vPro	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10A60017US	4x5	i5-4570	2GBx1	500G 7200	DVD±RW	None	None	HD 4600	None	None	Switch	vPro	G P	Win7 Pro64	06/18/13
10A60018US	4x5	i7-4770	4GBx1	1TB 7200	DVD±RW	Intel 105	None	HD 8470	USB	None	Switch	vPro	G P	Win7 Pro64 (DG)	06/18/13
10A60019US	4x5	i5-4570	4GBx1	500G 7200	DVD±RW	Intel 105	None	HD 4600	USB	None	Switch	vPro	G P	Win7 Pro64 (DG)	06/18/13
10A6001DUS	4x5	i5-4570	4GBx1	500G 7200	DVD	Intel 105	None	HD 4600	USB	None	Switch	vPro	G P	Win7 Pro64 (DG)	08/20/13
10A6001EUS	4x5	i7-4770	4GBx1	1TB 7200	DVD	Intel 105	None	HD 8470	USB	None	Switch	vPro	G P	Win7 Pro64 (DG)	08/20/13
10A6001FUS	4x5	i5-4570	2GBx1	500G 7200	DVD	None	None	HD 4600	None	None	Switch	vPro	G P	Win7 Pro64	08/20/13
10A6001SUS	4x5	i7-4770	4GBx1	500G 7200	DVD±RW	None	None	HD 4600	USB	Serial	None	vPro	G P	Win7 Pro64 (DG)	11/12/13
10A6001TUS	4x5	i5-4570	4GBx1	500G 7200	DVD±RW	None	None	HD 4600	None	None	None	vPro	G P	Win7 Pro64 (DG)	11/12/13

- Next Generation Intel platform with latest Intel vPro™ Technology and Intel Active Management Technology
- Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	<i>Ultimate security, stability, and manageability for the enterprise</i>											Preloaded operating system			
Processor	Intel® Core™ i5-4570 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), integrated Intel HD Graphics 4600, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Intel Core i7-4770 Processor (4 cores / 8 threads, 3.4GHz, 8MB cache), Turbo Boost 2.0 (3.9GHz), integrated Intel HD Graphics 4600, integrated 1600MHz dual-channel DDR3 memory controller, Virtualization Technology Processor in LGA1150 socket											Some: Windows® 7 Professional 64 Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit			
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)			
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3 , four 240-pin DIMM sockets											<ul style="list-style-type: none"> • Rescue and Recovery™ • Password Manager 			
Graphics	Intel HD Graphics 4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays, works along with discrete graphics to support up to five independent monitors; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking)</i> Some: AMD Radeon™ HD 8470 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one VGA, one DisplayPort, 25 watts, <i>Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz</i>											Preloaded applications (only some listed)			
DP dongle	None											<ul style="list-style-type: none"> • ThinkVantage® Product Recovery • ThinkVantage System Update • ThinkVantage Communication Utility • Desktop Power Manager • View Management Utility • Lenovo Cloud Storage by SugarSync • Lenovo Solution Center • Lenovo Message Center Plus • Norton™ Internet Security (30 days of virus definitions) • Adobe® Reader® • Skype™ • Microsoft Office preloaded; purchase a product key to activate • Cyberlink PowerDVD (DVD±RW, DVD) • Cyberlink Power2Go (DVD±RW) • Cyberlink PowerProducer (DVD±RW) • Evernote • Intel AppUp • Intel Small Business Advantage • Nitro Pro 			
Disk	SATA 6.0Gb/s 7200 rpm, 3.5" wide											Security <ul style="list-style-type: none"> • Security chip (see information on left) • One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) • Power-on password • Administrator password • Hard disk password • Boot sequence control • Boot without keyboard and mouse • Serial port I/O control • Individual USB port disablement • Chassis intrusion switch on selected model(s) 			
Optical	Some: DVD-ROM DL SATA 1.5Gb/s 16-48X Max ⁴ Drive Some: Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive														
SATA controller	Serial ATA, SATA 6.0Gb/s, integrated in chipset, RAID 0/1 support											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant ULE Gold Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to TC-AQP sheet; For Lenovo service upgrade options, please go to S-TC sheet			
Onboard SATA	Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s)														
eSATA port	None														
Media reader	None														
Chipset	Intel Q87 Express Chipset														
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)														
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), optional 2nd serial (9-pin), ethernet (RJ-45), one VGA, two DisplayPort, additional VGA, DisplayPort, or HDMI ports on optional graphic card on some models														
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)														
PCIe WLAN	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1														
Bluetooth	None														
Audio	High Definition (HD) Audio, Realtek® ALC662 codec														
Speaker	Internal speaker for business audio (1.5 watt)														
IEEE 1394	None														
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®														
Intel AMT	Intel Active Management Technology 9.0 (Intel AMT 9.0)														
Modem	None														
Security chip	Trusted Platform Module (TPM1.2-compliant)														
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo														
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo														
Power supply	280 watts, autosensing, 85% PSU														
Machine	<ul style="list-style-type: none"> • Mini Tower (25L), business black color, metal case • (WxDxH) 6.89" X 17.41" X 16.32"; 175mm X 442.3mm X 414.5mm • 24.69 lb (11.20 kg) in maximum configuration • Toolless cover removal, adapter retention • Toolless disk, optical drive removal 														
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 5.25", 1.6" high, access, open Bay 3: 3.5", 1" high, access, opt reader Bay 4: 3.5", 1" high, no access, std disk Bay 5: 3.5", 1" high, no access, opt disk														
Slot	Slot 1: half-length, full-height, PCIe 3.0 x16 (75w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x16 (x4 elec, 75w max) Slot 4: half-length, full-height, 32-bit PCI 2.3														
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available														



See footnotes for important warranty information

US model(s) announced June 18, 2013, August 20, 2013, or November 12, 2013

©Lenovo

(MSS1T-2) November 2013