


ThinkCentre M73 Mini Tower (10B1) - ES 5.2 (GMP)

Product Specifications Reference (PSREF)

Type-model	Slot x bay	Processor	Memory ^a	SATA disk GB rpm	SATA optical	PCIe WLAN	Media reader	Graphics	Chassis Intrusion switch	2nd Serial / Parallel	ENERGY STAR 5.2	Global (G) GMP (P)	Preload	Ann date (mm/dd/yy)
10B10011US	3x4	G3420	2GBx1	500G 7200	DVD	None	None	Intel HD	None	None	ES5.2	G P	Win7 Pro64	10/01/13
10B10012US	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	None	HD 4400	None	None	ES5.2	G P	Win7 Pro64 (DG)	10/01/13
10B10017US	3x4	i5-4570	4GBx1	1TB 7200	DVD±RW	N105	Media	HD 8470	Switch	None	ES5.2	G P	Win7 Pro64 (DG)	10/01/13
10B1001KUS	3x4	i3-4130	4GBx1	500G 7200	DVD±RW	None	None	HD 4400	None	None	ES5.2	G P	Win7 Pro64	02/04/14

● Part of the Global Models Plus (GMP) program with limited onsite service 3-year limited warranty

Positioning	<i>Essential business features, exceptional value</i>											Preloaded operating system		
Processor	Intel® Pentium® G3420 Processor (2 cores / 2 threads, 3.2GHz, 3MB cache), Intel HD Graphics, 1600MHz DDR3 memory controller Intel Core™ i3-4130 Processor (2 cores / 4 threads, 3.4GHz, 3MB cache), Intel HD Graphics 4400, 1600MHz DDR3 memory controller Intel Core i5-4570 Processor (4 cores / 4 threads, 3.2GHz, 6MB cache), Turbo Boost 2.0 (3.6GHz), Intel HD Graphics 4600, 1600MHz DDR3 memory controller Processor in LGA1150 socket											Some: Windows® 7 Professional 64 Some: Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit		
Implementation	Processor in LGA1150 socket											Ready to install applications (only some listed)		
Memory	16GB max, UDIMM, PC3-12800 1600MHz DDR3 , two 240-pin DIMM sockets *System automatically clocks down for processors with 1333MHz memory controller											<ul style="list-style-type: none"> ● Rescue and Recovery™ ● Password Manager 		
Graphics	Intel HD Graphics or Intel HD Graphics 4400/4600 in processor, uses main memory, one VGA, one DisplayPort™, supports dual independent display, works along with discrete graphics to support up to four independent monitors; <i>Maximum resolution: 2560x1600 (DisplayPort)@60Hz;</i> 1920x1200 (VGA)@60Hz (Reduced Blanking) Some: AMD Radeon™ HD 8470 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one VGA, one DisplayPort, 25 watts, <i>Max resolution: 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz</i>											Preloaded applications (only some listed) <ul style="list-style-type: none"> ● ThinkVantage® Product Recovery ● ThinkVantage System Update ● ThinkVantage Communication Utility ● ThinkVantage Power Manager ● View Management Utility ● PC Device Stage ● Lenovo Cloud Storage by SugarSync ● Lenovo Solution Center ● Lenovo Message Center Plus ● Norton™ Internet Security (30 days of virus definitions) ● Adobe® Reader® ● Skype™ ● Evernote® ● Microsoft® Office preloaded; purchase a product key to activate ● Cyberlink Power2Go (DVD±RW) ● Cyberlink PowerProducer (DVD±RW) ● Nitro Pro 		
Disk	Some: SATA 6.0Gb/s, 3.5" Wide, 7200 rpm											Security <ul style="list-style-type: none"> ● One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) ● Power-on password ● Administrator password ● Hard disk password ● Boot sequence control ● Boot without keyboard and mouse ● Serial port I/O control ● Individual USB port disablement ● Chassis intrusion switch on selected model(s) 		
Optical	Some: DVD-ROM DL SATA 1.5Gb/s Drive Some: Super Multi-Burner DL DVD±RW SATA 1.5Gb/s Drive													
SATA controller	Serial ATA, SATA 3.0Gb/s and SATA 6.0Gb/s, integrated in chipset													
Onboard SATA	SATA cables match SATA devices (each 1-drop to device), one SATA 3.0Gb/s connector (for optical) and two SATA 6.0Gb/s connectors (for HDD/SSD) on planar													
eSATA port	None											EPEAT™ Gold rating ENERGY STAR® 5.2-compliant Cisco EnergyWise compatible GREENGUARD® certified RoHS-compliant Supports ThinkVantage Technologies For compatible accessories, please go to TC-AQP sheet; For Lenovo service upgrade options, please go to S-TC sheet		
Media reader	Optional 9-in-1 media reader, internal USB 2.0													
Chipset	Intel H81 Express Chipset													
Front ports	Two USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)													
Rear ports	Two USB 3.0, two USB 2.0, serial (9-pin), optional 2nd serial (9-pin), optional parallel (9-pin), keyboard (PS/2), mouse (PS/2), ethernet (RJ-45), VGA DB-15, DisplayPort													
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone-in (stereo, 3.5mm)													
Audio	High Definition (HD) Audio, Realtek® ALC662 codec													
PCIe WLAN ⁴	Some: 11b/g/n wireless, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1													
Bluetooth	None													
Speaker	Internal speaker for business audio (1.5 watt)													
IEEE 1394	None													
Ethernet	Gigabit ethernet port, Realtek RTL8111GN, Wake on LAN®													
Manageability	Intel Standard Manageability													
Modem	None													
Security chip	None													
Keyboard	Preferred Pro USB Keyboard (USB connector), black, Lenovo® logo													
Mouse	Enhanced Optical USB Mouse, black, Lenovo logo													
Power supply	Some: 280 watts, autosensing, active PFC, 85% PSU													
Mechanical	<ul style="list-style-type: none"> ● Business black color; metal case ● 6.3" W X 16.6" D X 15.3" H (with handle) ● 160mm W X 422mm D X 388mm H ● 20.7 lb (9.4 kg) in maximum configuration ● Handle on top front ● Highlighted optical drive button for easy access 													
Bay	Bay 1: 5.25", 1.6" high, access, std optical Bay 2: 3.5", 1" high, no access, opt disk* Bay 3: 3.5", 1" high, no access, std disk Bay 4: 1.5", .35" high, access, opt reader* *bay only available on models with HDD/SSD/reader installed													
Slot	Slot 1: half-length, full-height, PCIe 3.0 x16 (60w max) Slot 2: half-length, full-height, PCIe 2.0 x1 Slot 3: half-length, full-height, PCIe 2.0 x1													
Limited Warranty	3-years, limited onsite service , 8 am-5 pm, Mon - Fri coverage excluding holidays, next business day response time / service upgrades available													

See footnotes for important warranty information
 US model(s) announced October 1, 2013 or February 4, 2014

©Lenovo
 (MLM1T-4) February 2014